

TOOL HOLDERS

CAT

BRIGHT-TOOLS

BRIGHT-TOOLS

BRIGHT-TOOLS

BRIGHT-TOOLS

BRIGHT-TOOLS



BRIGHT-TOOLS

BRIGHT-TOOLS

BRIGHT-TOOLS

CAT Taper Standard

CAT 锥柄标准



Size	D	d1	d2	d3	d4	d5	d6	d7	l1	l2	l3	l4	T
CAT30	1.812	1.25	2.176	1.531	1.25	0.516	0.645	0.2813	1.875	0.188	0.735	0.64	1/2-13
CAT40	2.500	1.75	2.863	2.219	1.75	0.641	0.645	0.2813	2.687	0.188	0.985	0.89	5/8-11
CAT50	3.875	2.75	4.238	3.594	2.75	1.020	1.020	0.2813	4.000	0.250	1.485	1.39	1-8

Taper standard: ANSI B5.50

Material: Alloyed case hardened steel

Surface Treatment: Blackening and Bright

Taper tolerance: <AT3

Hardness: HRC 56-60

Carbon depth: 0.8±0.2mm

Surface Roughness: Ra<0.2μm

Balancing: G6.3/15000; G2.5/25000

Cooling: AD; AD/B can be made by request.

CAT TOOLING SYSTEM

CAT 工具系统




ER Collet Chuck	F.04
ER弹簧夹头刀柄	
ER Collet Chuck,Short	F.04
ER弹簧夹头刀柄,超短型	
Power Milling Chuck.....	F.07
强力铣刀柄	
TG Collet Chuck.....	F.09
TG 超强力刀柄	
Face Mill Holder	F.10
面铣刀柄	
End Mill Holder.....	F.11
侧固刀柄	
Morse Taper Adapter	F.16
带扁尾莫氏刀柄	
Tool Holder Adatper Sleeve	F.16
转换刀柄	
Drill Chuck Adapter	F.17
钻接杆	
APU Drill Chuck Holder	F.17
APU钻夹头刀柄	
Precision Drill Chuck Holder	F.18
精密钻夹头刀柄	
Quick Change Tapping Chuck	F.18
弹性快换攻丝刀柄	
Screw-in Milling Cutter Holder.....	F.19
SOM 锁牙刀柄	
Runout Adjustable Flange Adapter.....	F.22
可调节精度法兰刀柄	
UM Adjustable	F.22
UM调零刀柄	
Boring Bar Blank	F.23
基础柄	
Test Arbor	F.23
主轴检测棒	
Alignment Tool for ATC Arm	F.24
调整机械手用组合模具	



CAT

ER Collet Chuck with UM Nut




ER 弹簧夹头刀柄



Size	D	D1	L	M	Capacity
CAT40-ER16UM-2.5"	44.45	32	2.5"	M10	1-10
CAT40-ER20UM-2.5"	44.45	35	2.5"	M14*1.5	1-13
CAT40-ER25-2.5"	44.45	42	2.5"	M18*1.5	2-16
CAT40-ER32-2.5"	44.45	50	2.5"	M22*1.5	2-20
CAT40-ER40-3"	50	63	3"	M28*1.5	3-26
CAT40-ER16UM-4"	28	32	4"	M10	1-10
CAT40-ER20UM-4"	34	35	4"	M14*1.5	1-13
CAT40-ER25-4"	42	42	4"	M18*1.5	2-16
CAT40-ER32-4"	44.45	50	4"	M22*1.5	2-20
CAT40-ER40-4"	50	63	4"	M28*1.5	3-26
CAT40-ER16UM-6"	28	32	6"	M10	1-10
CAT40-ER20UM-6"	34	35	6"	M14*1.5	1-13
CAT40-ER25-6"	42	42	6"	M18*1.5	2-16
CAT40-ER32-6"	44.45	50	6"	M22*1.5	2-20
CAT40-ER40-6"	50	63	6"	M28*1.5	3-26
CAT40-ER16UM-8"	28	32	8"	M10	1-10
CAT40-ER20UM-8"	34	35	8"	M14*1.5	1-13
CAT40-ER25-8"	42	42	8"	M18*1.5	2-16
CAT40-ER32-8"	44.45	50	8"	M22*1.5	2-20
CAT40-ER40-8"	50	63	8"	M28*1.5	3-26

ER Collet Chuck with UM Nut



ER 弹簧夹头刀柄



Size	D	D1	L	M	Capacity
CAT50-ER16UM-2"	28	32	2"	M10	1-10
CAT50-ER20UM-2"	25	35	2"	M14*1.5	1-13
CAT50-ER25-2"	32	42	2"	M18*1.5	2-16
CAT50-ER32-2"	40	50	2"	M22*1.5	2-20
CAT50-ER16UM-4"	28	32	4"	M10	1-10
CAT50-ER20UM-4"	34	35	4"	M14*1.5	1-13
CAT50-ER25-4"	42	42	4"	M18*1.5	2-16
CAT50-ER32-4"	50	50	4"	M22*1.5	2-20
CAT50-ER40-4"	63	63	4"	M28*1.5	3-26
CAT50-ER50-4"	69.85	78	4"	M36*1.5	6-34
CAT50-ER16UM-6"	28	32	6"	M10	1-10
CAT50-ER20UM-6"	34	35	6"	M14*1.5	1-13
CAT50-ER25-6"	42	42	6"	M18*1.5	2-16
CAT50-ER32-6"	50	50	6"	M22*1.5	2-20
CAT50-ER40-6"	63	63	6"	M28*1.5	3-26
CAT50-ER16UM-8"	28	32	8"	M10	1-10
CAT50-ER20UM-8"	34	35	8"	M14*1.5	1-13
CAT50-ER25-8"	42	42	8"	M18*1.5	2-16
CAT50-ER32-8"	50	50	8"	M22*1.5	2-20
CAT50-ER40-8"	63	63	8"	M28*1.5	3-26

ER Collet Chuck with Hex Nut


ER 弹簧夹头刀柄



Size	D	D1	L	M	Capacity
CAT40-ER11-2.5"	19	19	2.5"	M6	1-7
CAT40-ER16-2.5"	44.45	28	2.5"	M10	1-10
CAT40-ER20-2.5"	44.45	34	2.5"	M14*1.5	1-13
CAT40-ER11-4"	19	19	4"	M6	1-7
CAT40-ER16-4"	28	28	4"	M10	1-10
CAT40-ER20-4"	34	34	4"	M14*1.5	1-13
CAT40-ER11-6"	19	19	6"	M6	1-7
CAT40-ER16-6"	28	28	6"	M10	1-10
CAT40-ER20-6"	34	34	6"	M14*1.5	1-13
CAT40-ER16-8"	28	28	8"	M10	1-10
CAT40-ER20-8"	34	34	8"	M14*1.5	1-13
CAT50-ER16-2"	28	28	2"	M10	1-10
CAT50-ER20-2"	25	34	2"	M14*1.5	1-13
CAT50-ER16-4"	28	28	4"	M10	1-10
CAT50-ER20-4"	34	34	4"	M14*1.5	1-13
CAT50-ER16-6"	28	28	6"	M10	1-10
CAT50-ER20-6"	34	34	6"	M14*1.5	1-13
CAT50-ER16-8"	28	28	8"	M10	1-10
CAT50-ER20-8"	34	34	8"	M14*1.5	1-13

ER Collet Chuck, Short


ER 弹簧夹头刀柄, 超短型



Size	D	SW	L	L1
CAT40-ER25-1.1"	29.5	27	1.1"	0.35"
CAT40-ER32-1.1"	37.5	34	1.1"	0.35"

Power Milling Chuck 强力铣刀柄

NEW



Size	Type	d	D	D1	L	l	l1	l2	G
CAT40-CT16SA-90	1	0.630	1.772	1.750	3.543	2.559	-	0.787	M10
CAT40-CT20SA-90	1	0.787	2.047	1.750	3.543	3.150	-	0.591	M12
CAT40-CT20SA-105	1	0.787	2.047	1.750	4.134	3.150	-	0.591	M12
CAT40-CT20SA-120	1	0.787	2.047	1.750	4.724	3.150	-	0.591	M12
CAT40-CT25SA-105	1	0.984	2.402	1.750	4.134	3.150	-	0.591	M12
CAT40-CT25SA-120	1	0.984	2.402	1.750	4.724	3.150	-	0.591	M12
CAT40-CT25SA-135	1	0.984	2.402	1.750	5.315	3.150	-	0.591	M12
CAT40-CT32SA-105	2	1.260	2.874	1.750	4.134	3.346	0.906	0.787	M18
CAT40-CT32SA-120	2	1.260	2.874	1.750	4.724	3.346	0.906	0.787	M18
CAT40-CT32SA-135	2	1.260	2.874	1.750	5.315	4.724	-	0.787	M18
CAT50-CT16SA-90	1	0.630	1.772	2.750	3.543	2.559	-	0.787	M10
CAT50-CT16SA-105	1	0.630	1.772	2.750	4.134	2.559	-	0.787	M10
CAT50-CT20SA-90	1	0.787	2.047	2.750	3.543	3.150	-	0.591	M12
CAT50-CT20SA-105	1	0.787	2.047	2.750	4.134	3.150	-	0.591	M12
CAT50-CT20SA-135	1	0.787	2.047	2.750	5.315	3.150	-	0.591	M12
CAT50-CT25SA-105	1	0.984	2.402	2.750	4.134	3.150	-	0.591	M12
CAT50-CT25SA-135	1	0.984	2.402	2.750	5.315	3.150	-	0.591	M12
CAT50-CT25SA-165	1	0.984	2.402	2.750	6.496	3.150	-	0.591	M12
CAT50-CT32SA-95	1	1.260	2.874	2.750	3.740	4.724	-	0.787	M18
CAT50-CT32SA-105	1	1.260	2.874	2.750	4.134	4.724	-	0.787	M18
CAT50-CT32SA-120	1	1.260	2.874	2.750	4.724	4.724	-	0.787	M18
CAT50-CT32SA-135	1	1.260	2.874	2.750	5.315	4.724	-	0.787	M18
CAT50-CT32SA-150	1	1.260	2.874	2.750	5.906	4.724	-	0.787	M18
CAT50-CT32SA-165	1	1.260	2.874	2.750	6.496	4.724	-	0.787	M18
CAT50-CT42SA-105	1	1.654	3.465	2.750	4.134	4.724	-	0.787	M18
CAT50-CT42SA-120	1	1.654	3.465	2.750	4.724	4.724	-	0.787	M18
CAT50-CT42SA-135	1	1.654	3.465	2.750	5.315	4.724	-	0.787	M18
CAT50-CT42SA-150	1	1.654	3.465	2.750	5.906	4.724	-	0.787	M18
CAT50-CT42SA-165	1	1.654	3.465	2.750	6.496	4.724	-	0.787	M18

CAT


TG Collet Chuck

TG 超强力刀柄

A ↗
≤0.005

RPM
G2.5/20000

AD



Size	D	L	Collet	Capacity
CAT40-TG75-2.54"	1.968"	2.54"	TG 75	0.094 - 0.75"
CAT40-TG100-2.76"	2.362"	2.76"	TG 100	0.094 - 1.0"

CAT

RPM
G6.3/15000

Size	D	L	Collet	Capacity
CAT50-TG75-2.54"	1.968"	2.54"	TG 75	0.094 - 0.75"
CAT50-TG100-3.26"	2.362"	3.26"	TG 100	0.094 - 1.0"


Precision Screw Collet Chuck

NDC 后拉刀柄

A ↗
≤0.003

RPM
G2.5/25000

AD
AD




Size	D	D1	L	L1
CAT40-NDC14-70	50	30	70	26
CAT40-NDC14-115	50	30	115	63.7
CAT40-NDC14-145	50	30	145	91
CAT40-NDC20-70	50	40	70	31
CAT40-NDC20-115	50	40	115	69.7
CAT40-NDC20-145	50	40	145	102.3
CAT50-NDC14-110	53	30	110	21.5
CAT50-NDC20-110	53	40	110	26.5
CAT50-NDC20-155	53	40	155	66.7
CAT50-NDC32-150	63	63	150	118

CAT

Face Mill Holder Inch 英制面铣刀柄

A ↗	RPM
≤0.005	G2.5/25000




Size	d	D	L	H	M	W
CAT40-FMA1/2"-1.75"	1/2"	36.5	1.75"	13.97	1/4-28	6.35
CAT40-FMA3/4"-1.75"	3/4"	44.45	1.75"	17.45	3/8-24	7.93
CAT40-FMA1"-2"	1"	57.15	2"	17.45	1/2-20	9.525
CAT40-FMA1-1/4"-2"	1-1/4"	69.85	2"	17.45	5/8-18	12.7
CAT40-FMA1-1/2"-2"	1-1/2"	78	2"	23.87	3/4-16	15.875
CAT40-FMA1/2"-4"	1/2"	36.5	4"	13.97	1/4-28	6.35
CAT40-FMA3/4"-4"	3/4"	44.45	4"	17.45	3/8-24	7.93
CAT40-FMA1"-4"	1"	57.15	4"	17.45	1/2-20	9.525
CAT40-FMA1-1/4"-4"	1-1/4"	69.85	4"	17.45	5/8-18	12.7
CAT40-FMA1-1/2"-4"	1-1/2"	78	4"	23.87	3/4-16	15.875
CAT40-FMA3/4"-6"	3/4"	44.45	6"	17.45	3/8-24	7.93
CAT40-FMA1"-6"	1"	57.15	6"	17.45	1/2-20	9.525
CAT40-FMA3/4"-8"	3/4"	44.45	8"	17.45	3/8-24	7.93
CAT40-FMA1"-8"	1"	57.15	8"	17.45	1/2-20	9.525
CAT50-FMA1/2"-1.38"	1/2"	36.5	1.38"	13.97	1/4-28	6.35
CAT50-FMA3/4"-2"	3/4"	44.45	2"	17.45	3/8-24	7.93
CAT50-FMA1"-2"	1"	57.15	2"	17.45	1/2-20	9.525
CAT50-FMA1-1/4"-2"	1-1/4"	69.85	2"	17.45	5/8-18	12.7
CAT50-FMA1-1/2"-2"	1-1/2"	78	2"	23.87	3/4-16	15.875
CAT50-FMA2"-2"	2"	98	2"	36	1-14	19.05
CAT50-FMA3/4"-4"	3/4"	44.45	4"	17.45	3/8-24	7.93
CAT50-FMA1"-4"	1"	57.15	4"	17.45	1/2-20	9.525
CAT50-FMA1-1/4"-4"	1-1/4"	69.85	4"	17.45	5/8-18	12.7
CAT50-FMA1-1/2"-4"	1-1/2"	78	4"	23.87	3/4-16	15.875
CAT50-FMA2"-4"	2"	98	4"	36	1-14	19.05
CAT50-FMA3/4"-6"	3/4"	44.45	6"	17.45	3/8-24	7.93
CAT50-FMA1"-6"	1"	57.15	6"	17.45	1/2-20	9.525
CAT50-FMA1-1/4"-6"	1-1/4"	69.85	6"	17.45	5/8-18	12.7
CAT50-FMA1-1/2"-6"	1-1/2"	78	6"	23.87	3/4-16	15.875
CAT50-FMA3/4"-8"	3/4"	44.45	8"	17.45	3/8-24	7.93
CAT50-FMA1"-8"	1"	57.15	8"	17.45	1/2-20	9.525
CAT50-FMA1-1/4"-8"	1-1/4"	69.85	8"	17.45	5/8-18	12.7
CAT50-FMA1-1/2"-8"	1-1/2"	78	8"	23.87	3/4-16	15.875

End Mill Holder Weldon 侧固刀柄



			
DIN6359/1835B	≤ 0.005	G2.5/20000	AD



Size	d	D	L
CAT40-SLA1/8"-1.38"	1/8"	17.526	1.38"
CAT40-SLA3/16"-1.38"	3/16"	17.526	1.38"
CAT40-SLA1/4"-1.38"	1/4"	19.81	1.38"
CAT40-SLA5/16"-1.38"	5/16"	22.225	1.38"
CAT40-SLA3/8"-1.38"	3/8"	44.45	1.38"
CAT40-SLA1/2"-1.75"	1/2"	31.75	1.75"
CAT40-SLA5/8"-1.75"	5/8"	38.1	1.75"
CAT40-SLA3/4"-1.75"	3/4"	44.45	1.75"
CAT40-SLA7/8"-1.75"	7/8"	47.625	1.75"
CAT40-SLA1"-1.75"	1"	50.8	1.75"
CAT40-SLA1-1/4"-2"	1-1/4"	57.15	2"
CAT40-SLA1/8"-2.5"	1/8"	17.526	2.5"
CAT40-SLA3/16"-2.5"	3/16"	17.526	2.5"
CAT40-SLA1/4"-2.5"	1/4"	19.81	2.5"
CAT40-SLA5/16"-2.5"	5/16"	22.225	2.5"
CAT40-SLA3/8"-2.5"	3/8"	25.4	2.5"
CAT40-SLA7/16"-2.5"	7/16"	28.575	2.5"
CAT40-SLA1/2"-2.5"	1/2"	31.75	2.5"
CAT40-SLA5/8"-3"	5/8"	38.1	3"
CAT40-SLA3/4"-3"	3/4"	44.45	3"
CAT40-SLA7/8"-3.5"	7/8"	47.625	3.5"
CAT40-SLA1"-3"	1"	50.8	2"


CAT

End Mill Holder Weldon

侧固刀柄



			
DIN6359/1835B	≤0.005	G2.5/20000	AD




Size	d	D	L
CAT40-SLA1/8"-4"	1/8"	17.526	4"
CAT40-SLA3/16"-4"	3/16"	17.526	4"
CAT40-SLA1/4"-4"	1/4"	19.81	4"
CAT40-SLA5/16"-4"	5/16"	22.225	4"
CAT40-SLA3/8"-4"	3/8"	25.4	4"
CAT40-SLA1/2"-4"	1/2"	31.75	4"
CAT40-SLA5/8"-4"	5/8"	38.1	4"
CAT40-SLA3/4"-4"	3/4"	44.45	4"
CAT40-SLA1"-4"	1"	50.8	4"
CAT40-SLA1-1/4"-4"	1-1/4"	63.5	4"
CAT40-SLA1-1/2"-4"	1-1/2"	66.675	4"
CAT40-SLA1/4"-6"	1/4"	19.81	6"
CAT40-SLA5/16"-6"	5/16"	22.225	6"
CAT40-SLA3/8"-6"	3/8"	25.4	6"
CAT40-SLA1/2"-6"	1/2"	31.75	6"
CAT40-SLA5/8"-6"	5/8"	38.1	6"
CAT40-SLA3/4"-6"	3/4"	44.45	5.5"
CAT40-SLA7/8"-6"	7/8"	47.625	6"
CAT40-SLA1"-6"	1"	50.8	6"
CAT40-SLA1-1/4"-6"	1-1/4"	63.5	6"
CAT40-SLA1-1/2"-6"	1-1/2"	66.675	6"

End Mill Holder Weldon

侧固刀柄



			
DIN6359/1835B	≤0.005	G2.5/15000	AD




Size	d	D	L
CAT50-SLA3/16"-2.5"	3/16"	17.526	2.5"
CAT50-SLA1/4"-2.5"	1/4"	19.81	2.5"
CAT50-SLA5/16"-2.5"	5/16"	22.225	2.5"
CAT50-SLA3/8"-2.5"	3/8"	25.4	2.5"
CAT50-SLA7/16"-2.5"	7/16"	28.575	2.5"
CAT50-SLA1/2"-2.62"	1/2"	31.75	2.62"
CAT50-SLA5/8"-3"	5/8"	38.1	3"
CAT50-SLA3/4"-3"	3/4"	44.45	3"
CAT50-SLA1"-2"	1"	50.8	2"
CAT50-SLA1-1/4"-2"	1-1/4"	69.85	2"
CAT50-SLA1-1/2"-2.25"	1-1/2"	66.675	2.25"
CAT50-SLA2"-5.62"	2"	95.25	5.62"
CAT50-SLA1/4"-4"	1/4"	19.81	4"
CAT50-SLA5/16"-4"	5/16"	22.225	4"
CAT50-SLA3/8"-4"	3/8"	25.4	4"
CAT50-SLA7/16"-4"	7/16"	28.575	4"
CAT50-SLA1/2"-4"	1/2"	31.75	4"
CAT50-SLA5/8"-4"	5/8"	38.1	4"
CAT50-SLA3/4"-4"	3/4"	44.45	4"
CAT50-SLA7/8"-4"	7/8"	47.625	4"
CAT50-SLA1"-4"	1"	50.8	4"
CAT50-SLA1-1/4"-4"	1-1/4"	63.5	4"
CAT50-SLA1-1/2"-4"	1-1/2"	66.675	4"
CAT50-SLA1/4"-6"	1/4"	19.81	6"
CAT50-SLA5/16"-6"	5/16"	22.225	6"
CAT50-SLA3/8"-6"	3/8"	25.4	6"
CAT50-SLA7/16"-6"	7/16"	28.575	6"
CAT50-SLA1/2"-6"	1/2"	31.75	6"
CAT50-SLA5/8"-6"	5/8"	38.1	6"
CAT50-SLA3/4"-6"	3/4"	44.45	6"
CAT50-SLA7/8"-6"	7/8"	47.625	6"
CAT50-SLA1"-6"	1"	50.8	6"
CAT50-SLA1-1/4"-6"	1-1/4"	63.5	6"
CAT50-SLA1-1/2"-6"	1-1/2"	66.675	6"

End Mill Holder with Coolant Channels

侧固刀柄，端面出水型

			
DIN6359/1835B	≤0.005	G2.5/20000	AD




Size	d	D	L
CAT40-SLA1/8"-2.5"K	1/8"	17.526	2.5"
CAT40-SLA3/16"-2.5"K	3/16"	17.526	2.5"
CAT40-SLA1/4"-2.5"K	1/4"	19.81	2.5"
CAT40-SLA3/8"-2.5"K	3/8"	25.4	2.5"
CAT40-SLA7/16"-2.5"K	7/16"	28.575	2.5"
CAT40-SLA1/2"-2.5"K	1/2"	31.75	2.5"
CAT40-SLA5/8"-3"K	5/8"	38.1	3"
CAT40-SLA3/4"-3"K	3/4"	44.45	3"
CAT40-SLA7/8"-3.5"K	7/8"	47.625	3.5"
CAT40-SLA1"-3"K	1"	50.8	2"
CAT40-SLA1/8"-4"K	1/8"	17.526	4"
CAT40-SLA3/16"-4"K	3/16"	17.526	4"
CAT40-SLA1/4"-4"K	1/4"	19.81	4"
CAT40-SLA5/16"-4"K	5/16"	22.225	4"
CAT40-SLA3/8"-4"K	3/8"	25.4	4"
CAT40-SLA1/2"-4"K	1/2"	31.75	4"
CAT40-SLA1"-4"K	1"	50.8	4"
CAT40-SLA1-1/4"-4"K	1-1/4"	63.5	4"
CAT40-SLA1-1/2"-4"K	1-1/2"	66.675	4"
CAT40-SLA5/16"-6"K	5/16"	22.225	6"
CAT40-SLA3/8"-6"K	3/8"	25.4	6"
CAT40-SLA1/2"-6"K	1/2"	31.75	6"
CAT40-SLA5/8"-6"K	5/8"	38.1	6"
CAT40-SLA3/4"-6"K	3/4"	44.45	6"
CAT40-SLA1"-6"K	1"	50.8	6"
CAT40-SLA1-1/4"-6"K	1-1/4"	63.5	6"
CAT40-SLA1-1/2"-6"K	1-1/2"	66.675	6"

CAT

End Mill Holder with Coolant Channels

侧固刀柄，端面出水型


			
DIN6359/1835B	≤ 0.005	G2.5/15000	AD




Size	d	D	L
CAT50-SLA1/4"-2.5"K	1/4"	19.81	2.5"
CAT50-SLA5/16"-2.5"K	5/16"	22.225	2.5"
CAT50-SLA3/8"-2.5"K	3/8"	25.4	2.5"
CAT50-SLA7/16"-2.5"K	7/16"	28.575	2.5"
CAT50-SLA1/2"-2.62"K	1/2"	31.75	2.62"
CAT50-SLA5/8"-3"K	5/8"	38.1	3"
CAT50-SLA3/4"-3"K	3/4"	44.45	3"
CAT50-SLA1"-2"K	1"	50.8	2"
CAT50-SLA1-1/2"- 2.25"K	1-1/2"	66.675	2.25"
CAT50-SLA2"-5.62"K	2"	95.25	5.62"
CAT50-SLA1/4"-4"K	1/4"	19.81	4"
CAT50-SLA5/16"-4"K	5/16"	22.225	4"
CAT50-SLA3/8"-4"K	3/8"	25.4	4"
CAT50-SLA7/16"-4"K	7/16"	28.575	4"
CAT50-SLA1/2"-4"K	1/2"	31.75	4"
CAT50-SLA5/8"-4"K	5/8"	38.1	4"
CAT50-SLA3/4"-4"K	3/4"	44.45	4"
CAT50-SLA7/8"-4"K	7/8"	47.625	4"
CAT50-SLA1"-4"K	1"	50.8	4"
CAT50-SLA1-1/4"-4"K	1-1/4"	63.5	4"
CAT50-SLA1-1/2"- 4"K	1-1/2"	66.675	4"
CAT50-SLA1/4"-6"K	1/4"	19.81	6"
CAT50-SLA5/16"-6"K	5/16"	22.225	6"
CAT50-SLA3/8"-6"K	3/8"	25.4	6"
CAT50-SLA7/16"-6"K	7/16"	28.575	6"
CAT50-SLA1/2"-6"K	1/2"	31.75	6"
CAT50-SLA5/8"-6"K	5/8"	38.1	6"
CAT50-SLA3/4"-6"K	3/4"	44.45	6"
CAT50-SLA7/8"-6"K	7/8"	47.625	6"
CAT50-SLA1"-6"K	1"	50.8	6"
CAT50-SLA1-1/4"-6"K	1-1/4"	63.5	6"
CAT50-SLA1-1/2"- 6"K	1-1/2"	66.675	6"

Morse Taper Adapter with Tang 带扁尾莫氏刀柄



 DIN6383	 A ≤ 0.005	 RPM G2.5/25000
---	--	---




Size	MT. NO.	D	L
CAT40-MTA1-1.75"	1	25.40	1.75"
CAT40-MTA2-2"	2	31.75	2"
CAT40-MTA3-3"	3	41.45	3"
CAT40-MTA4-4"	4	50.80	4"
CAT50-MTA2-2"	2	31.75	2"
CAT50-MTA3-2"	3	41.45	2"
CAT50-MTA4-3"	4	50.80	3"
CAT50-MTA5-4"	5	69.85	4"

Tool Holder Adapter Sleeve 转换刀柄



 A ≤ 0.005	 AD
--	--




Size	D1	D2	L
CAT30-HSK32C-45	32	37	45
CAT30-HSK40C-60	40	45	60
CAT40-HSK32C-50	32	37	50
CAT40-HSK40C-50	40	45	50
CAT40-HSK50C-60	50	55	60
CAT40-HSK63C-75	63	70	75
CAT50-HSK32C-50	32	37	50
CAT50-HSK40C-50	40	45	50
CAT50-HSK50C-55	50	55	55
CAT50-HSK63C-55	63	70	55
CAT50-HSK80C-80	80	87	80
CAT50-HSK100C-95	100	110	95

Drill Chuck Adapter 钻接杆




 DIN238	 A ≤ 0.005	RPM G2.5/25000
--	--	-------------------



Size	D	L
CAT40-JT2-1.5"	14.199	1.5"
CAT40-JT3-1.5"	20.599	1.5"
CAT40-JT4-1.5"	28.55	1.5"
CAT40-JT6-1.5"	17.17	1.5"
CAT40-JT33-1.5"	15.85	1.5"
CAT50-JT2-1.5"	14.199	1.5"
CAT50-JT3-1.5"	20.599	1.5"
CAT50-JT4-1.5"	28.55	1.5"
CAT50-JT6-1.5"	17.17	1.5"
CAT50-JT33-1.5"	15.85	1.5"

CAT

APU Drill Chuck Holder APU 钻夹头刀柄




Size	D	L	Capacity
CAT40-APU08-85	37	85	1-8
CAT40-APU13-100	50	100	1-13
CAT40-APU16-110	54.5	110	3-16
CAT50-APU13-100	50	100	1-13
CAT50-APU16-105	54.5	105	3-16

Precision Drill Chuck Holder

精密钻夹头刀柄



A ↗	RPM
≤0.03	G2.5/25000




Size	D	D1	L	L1	Capacity
CAT40-CPU10-80	38	-	80	28.9	1-10
CAT40-CPU13-90	50	-	90	-	1-13
CAT40-CPU16-90	50	-	90	-	1-16
		-			
CAT50-CPU13-100	50	-	100	-	1-13
CAT50-CPU16-100	50	-	100	-	1-16

CAT

Quick Change Tapping Chuck with Length Compensation

弹性快换攻丝刀柄




Size	D	d	L	T	C
CAT40-TC312-65	36	19	65	7.5	7.5
CAT40-TC820-93	54	31	93	12.5	12.5
CAT40-TC1433-156	78	48	156	22	22
CAT50-TC312-100	36	19	100	7.5	7.5
CAT50-TC820-100	54	31	100	12.5	12.5
CAT50-TC1433-142	78	48	142	22	22

Screw-in Milling Cutter Holder

锁牙刀柄，锥柄型



A ↗ ≤0.005	RPM G6.3/15000	AD
---------------	-------------------	----



Size	M	d1	d2	D	L	L1
CAT40-SOM08-44 L=25	8	8.5	14.5	15	44	25
CAT40-SOM08-69 L=50	8	8.5	14.5	23	69	50
CAT40-SOM08-94 L=75	8	8.5	14.5	23	94	75
CAT40-SOM08-119 L=100	8	8.5	14.5	25	119	100
CAT40-SOM10-24 L=5	10	10.5	18	18	24	5
CAT40-SOM10-44 L=25	10	10.5	18	20	44	25
CAT40-SOM10-69 L=50	10	10.5	18	23	69	50
CAT40-SOM10-94 L=75	10	10.5	18	28	94	75
CAT40-SOM10-119 L=100	10	10.5	18	32	119	100
CAT40-SOM10-169 L=150	10	10.5	18	36.5	169	150
CAT40-SOM12-24 L=5	12	12.5	21	21	24	5
CAT40-SOM12-44 L=25	12	12.5	21	24	44	25
CAT40-SOM12-69 L=50	12	12.5	21	24	69	50
CAT40-SOM12-94 L=75	12	12.5	21	31	94	75
CAT40-SOM12-119 L=100	12	12.5	21	33	119	100
CAT40-SOM12-144 L=125	12	12.5	21	36	144	125
CAT40-SOM12-169 L=150	12	12.5	21	40	169	150
CAT40-SOM16-24 L=5	16	17	29	29	24	5
CAT40-SOM16-44 L=25	16	17	29	29	44	25
CAT40-SOM16-69 L=50	16	17	29	34	69	50
CAT40-SOM16-94 L=75	16	17	29	34	94	75
CAT40-SOM16-119 L=100	16	17	29	36	119	100
CAT40-SOM16-144 L=125	16	17	29	40	144	125
CAT40-SOM16-169 L=150	16	17	29	42.5	169	150


CAT

Screw-in Milling Cutter Holder

锁牙刀柄，锥柄型



A ↗	RPM	
≤0.005	G6.3/15000	AD



Size	M	d1	d2	D	L	L1
CAT50-SOM08-69 L=50	8	8.5	14.5	23	69	50
CAT50-SOM08-119 L=100	8	8.5	14.5	25	119	100
CAT50-SOM08-169 L=150	8	8.5	14.5	30	169	150
CAT50-SOM10-69 L=50	10	10.5	18	23	69	50
CAT50-SOM10-119 L=100	10	10.5	18	32	119	100
CAT50-SOM10-169 L=150	10	10.5	18	36.5	169	150
CAT50-SOM12-69 L=50	12	12.5	21	24	69	50
CAT50-SOM12-119 L=100	12	12.5	21	33	119	100
CAT50-SOM12-169 L=150	12	12.5	21	40	169	150
CAT50-SOM16-69 L=50	16	17	29	34	69	50
CAT50-SOM16-119 L=100	16	17	29	36	119	100
CAT50-SOM16-169 L=150	16	17	29	42.5	169	150

BRIGHT-TOOLS

BRIGHT-TOOLS

BRIGHT-TOOLS

BRIGHT-TOOLS

Screw-in Milling Cutter Holder


锁牙刀柄，直柄型



A ↗
≤0.005

RPM
G6.3/15000

AD



Size	M	d1	d2	L	L1
CAT40-M10-119 L=100	10	10.5	18	119	100
CAT40-M10-169 L=150	10	10.5	18	169	150
CAT40-M12-119 L=100	12	12.5	21	119	100
CAT40-M12-144 L=125	12	12.5	21	144	125
CAT40-M12-169 L=150	12	12.5	21	169	150
CAT40-M16-119 L=100	16	17	29	119	100
CAT40-M16-144 L=125	16	17	29	144	125
CAT40-M16-169 L=150	16	17	29	169	150
CAT50-M10-119 L=100	10	10.5	18	119	100
CAT50-M10-169 L=150	10	10.5	18	169	150
CAT50-M12-119 L=100	12	12.5	21	119	100
CAT50-M12-169 L=150	12	12.5	21	169	150
CAT50-M16-119 L=100	16	17	29	119	100
CAT50-M16-169 L=150	16	17	29	169	150


CAT

Runout Adjustable Flange Adapter

可调节精度法兰刀柄

A ↗
≤0.002

RPM
G2.5/25000




Size	D	D1	D2	L	G	G1
CAT40-MOD060-050	60	30	44	50	M5	M8x1
CAT40-MOD070-050	70	35	53	50	M6	M8x1
CAT40-MOD080-055	80	40	63	55	M6	M8x1
CAT40-MOD100-060	100	50	79	60	M8	M10x1
CAT50-MOD060-050	60	30	44	50	M5	M8x1
CAT50-MOD070-050	70	35	53	50	M6	M8x1
CAT50-MOD080-050	80	40	63	50	M6	M8x1
CAT50-MOD100-060	100	50	79	60	M8	M10x1
CAT50-MOD117-060	117	60	96	60	M8	M10x1
CAT50-MOD140-060	140	80	119	60	M10	M10x1

UM Adjustable Tool Holder

UM 调零刀柄

A ↗
≤0.003


RPM
G2.5/25000



Size	D1	D2	D3	L
CAT40-UM12-65	12	28	44.5	65
CAT40-UM16-80	16	32	48	80
CAT40-UM20-90	20	40	53	90
CAT40-UM25-100	25	48	63	100
CAT40-UM32-105	32	52	63	105
CAT50-UM12-80	12	28	44.5	80
CAT50-UM16-80	16	32	48	80
CAT50-UM20-90	20	40	53	90
CAT50-UM25-100	25	48	63	100
CAT50-UM32-105	32	52	63	105

Boring Bar Blank

基础柄





Size	D	L
CAT40-2.5"-6"	2.5"	6"
CAT40-2.5"-10"	2.5"	10"
CAT40-4"-6"	4"	6"
CAT40-4"-10"	4"	10"
CAT50-2.5"-6"	2.5"	6"
CAT50-2.5"-10"	2.5"	10"
CAT50-4"-6"	4"	6"
CAT50-4"-10"	4"	10"
CAT50-6"-10"	6"	10"

Other sizes can be made by request.

CAT

Test Arbor


主轴检测棒



Size	D	L
CAT30-32-250	32	250
CAT40-40-300	40	300
CAT50-50-300	50	300


Other sizes can be made by request.

Alignment Tool for ATC Arm 调整机械手用组合模具



Size	D	D1	D2	L	L1	L2	L3	M
CAT30-ATC-18D	31.75	46	18	50.8	3.175	20	15.875	M12
CAT40-ATC-20D	44.45	63.5	20	71.43	3.175	25	15.875	M12
CAT50-ATC-28D	69.85	98.43	28	104.78	3.175	35	15.875	M16

Alignment Tool for ATC Arm 调整机械手用组合模具



Size	D	D1	D2	L	L1	L2	L3	L4	L5
CAT40-ATC20	36.5	44.45	20	71.425	3.175	15.875	23	251	44
CAT50-ATC28	98.43	69.85	28	104.775	3.175	15.875	35	261	54

Usage:

1. Install the calibration taper to the machine spindle.
2. Install the calibration flange on the ATC machine.
3. Insert the calibration pin into the calibration flange.
4. Rotate the calibration pin to find the maximum and minimum positions of the pointer.
value position of the pointer. This direction is the direction of eccentricity, and the amount of eccentricity is half of the difference.
5. Adjust the ATC manipulator and ensure that the front of the calibration pin is fully inserted into the flange.

使用方法

1. 将校正锥柄安装到机床主轴。
2. 将校正法兰安装在 ATC 机械手上。
3. 将校正销棒插入校正法兰。
4. 旋转校正销棒，找到指针的最大值位置和最小值位置。
该方向即偏心方向，偏心量为差值的一半。
5. 调整 ATC 机械手并确保校正销棒前端完全插入法兰中。